

Mechanical Adaptivity as a Process: Implications to New Materials and Material System Design

***Matt Smith, Hilmar Koerner, Conner Stone, Robert Strong,
Kyungmin Lee, Timothy J. White, David Wang, Loon-Seng Tan
Richard A. Vaia***

*Functional Materials Division
Materials and Manufacturing Directorate*

Funding: Air Force Office of Scientific Research
AFRL Materials & Manufacturing Directorate




Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE AUG 2011		2. REPORT TYPE		3. DATES COVERED 00-00-2011 to 00-00-2011	
4. TITLE AND SUBTITLE Mechanical Adaptivity as a Process: Implications to New Materials and Material System Design				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory,Functional Materials Division,Materials and Manufacturing Directorate,Wright Patterson AFB,OH,45433				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at the 2nd Multifunctional Materials for Defense Workshop in conjunction with the 2012 Annual Grantees'/Contractors' Meeting for AFOSR Program on Mechanics of Multifunctional Materials & Microsystems Held 30 July - 3 August 2012 in Arlington, VA. Sponsored by AFRL, AFOSR, ARO, NRL, ONR, and ARL.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 24	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

What is Mechanical Adaptivity?




Energy Transduction Process Producing Force or Motion

- Conversion of Energy to Work
- Store Mechanical Energy and Release
- Combination



Mechanical Design Analogy:



Simple
Machines



Mechanical Design



Advanced
Functions



Building Blocks

Materials that display:

- 1) Autonomous behavior
- 2) Respond to multiple stimuli
- 3) 3D, rapid actuation

Knowledge & Predictive Models

Accurate math models
enable predictive design

Fabrication of Architecture: Greater than sum of the parts

Architecture design with responsive
materials leading to enhanced
functionality

Program Status




Building Blocks

HT Thermal Shape Memory




w/ L-S Tan, AFRL

PhotoChem-Mechanical






w/ T. White & L-S Tan, AFRL

Autonomic Chemo-Mechanical





Predictive Models



w/ A. Balazs, UPitt
M. Smith, Hope C.

Fabrication of Devices



w/ T.White & M. Smith, Hope C.






Photo Mechanical: Aerospace Applications




Beam Steering



Ar+ blocked


 $I = 4 \text{ mW/cm}^2$

Tabiryan et al BEAM
Unpublished. Bunning,
Optics Express, 2009.
Tabiryan & White
Optic Express 2010




Tuning Receivers and Packages




3D Photovoltaics



Nuzzo et al., *PNAS* 106
2009



Vaia et al 2012




John Hart, Davor Copic,
University of Michigan

Remote & Focused Trigger



PhotoChem-Mechanical Response: Azo



Isomerization:





“Glassy” Networks: Azo & LC



White, et al AFRL 2008

Elastomers: LC-Azo







Tuning Photo-Mechanical Response with Process History





Photo-Plastic (Photo Set, Photo Hardening)
Remove light, retain shape

Photo-Elastic (Photo Recovery)
Remove light, recovery original shape






Rapid Quench


Slow Quench



Glass Structure




	T_g [K]	Δh [kJ/mol]	β	M
CP2	498	975	0.84	108
azo-5-CP2	500	980	0.71	110
azo-20-CP2	505	1500	0.46	150



Molecular Dynamics




442 nm



Trans-
isomer




Cis-
isomer




- Isotropic trans distribution
- 442 illumination:
 - trans rotation + 3-5 % cis
 - RQ > SQ
 - Reversible & $\perp E$
- Dark state:
 - RQ partial recovery consistent with cis, trans enhancement
 - SQ initial state recovery

Relative Abs: Trans Isomer (355 nm)




RQ



SQ




Glass Energy Landscape for Photo Chemical to Mechanical Transduction




Photon to Isomerization

$$e \sim S f_{\text{isom}}$$




Internal Energy Storage & Recovery

$$\frac{\epsilon_{\text{plastic}}}{\epsilon_{\text{elastic}}} \sim f\left(\frac{U_a}{kT}\right)$$



Recovery Rates



Implications & Next Steps



Distribution of local “activation volume” controls first step for molecular to macroscopic transduction

- Molecular structure **and** process history
- Fraction of successful photon-to-isomerization events
- Fraction of trapped events
- Rate of recovery of events


Material System Architecture to Optimize Speed and Efficiency

- $DU \sim r$ (isomerization) $I(x) E(x)$
- Local anisotropy – LCs v. semi-rigid v. flexible chains
- Network structure, secondary relaxations, local of “hinge”
- Photochemistry: rotation v. cis formation



Telechelic Chain










n-functional Crosslink



X:





R₁:



Autonomic Chem-Mechanical Systems: Responsive Hydrogels & Chemical Oscillators



Responsive Hydro-gels




Chemical Oscillator


Stirred BZ reaction




BZ Reaction




M. Smith



Maeda et al. *Int. J. Mol. Sci.* 2010



R. Yoshida



Tabata et al. *Sensor Actuat. A* 2002

Heterogeneous Chem-Mechanical Design




Heterogeneous Autonomic Systems = Composite w/ Active & Inactive Regions


- Homogenous Autonomic Gel = Strain Generator Unit
- Amplify Motion through mechanical architecture
- Coupled feedback through
Chemical Concentration gradients
Mechanical-Chem interactions

Potential routes for control

Photo Directed Motion




Oscillating Elasticity




Ru gradient

$L > 1\text{mm}$



Coupled Oscillator patches:

2D patterning allows for phase control of



Balazs et al. *Prog. Polym. Sci.* **35** 2010



(40°C)
Side view


Westbrook and Qi. *J. Intell. Mater. Sys. Struct.* **19** 2008

Patterning Structure and Active Regions




Assembly - arrange premade, discrete homogenous units

- Adv: Flexibility in design
- Dis: minimal mechanical coupling, weak structures, very slow, poor reproducibility




Showalter et al. *Science* **323** 2009
Steinbock et al. *Science*, **269** 1995


Steinbock et al. *J. Phys. Chem.* **100** 1996



Yashin, et al
J.Mater.Chem.,
2012



Van Vliet, *Adv. Func. Mater.*, 2012




Photopolym - in plane patterning of monomer mixture

- Adv: Precision control to micron scale
- Dis: catalyst photo sensitive, limited flexibility (new form for new app)

Postfunctionalization - separate form from pattern (add catalyst & x-linking later)

- Adv: Flexible for 2D (on-demand stamping), Pattern 3D structures
- Dis: Completeness of reaction, profiles dependent on diffusion



Jacobsen et al. *Adv. Mater.* **19** 2007



Vaia, Smith, *SPIE* 2012



Additive Manufacturing – printing 3D (involve postfunctionalization, thermo-gelling, etc..)

- Adv: 3D structures (additive manufacturing)
- Dis: Resolution limits, processing variables




Vaia, et al 2012

Postfunctionalization: Polyacrylamide




Polymer *or*
Swollen Network




Immerse in BZ Soln

0.08M Sodium
Bromate
0.04M Malonic Acid
0.7M Nitric Acid





Literature: Typical strains = 2-20%








Patterning poly(AAm-co-APMA)

Process: stamping



Gel Cross Section - Ru Gradient



Large Circular Pattern

Chemical wave periods: 4-10min



Current Challenge: Improve control over diffusion and pattern size

BZ-Gelatin for Thermogelling

Thermogel


- physically crosslinked (H-bonds, xystals)
- melts above a critical temperature

Type A BZ Gelatin




Ru conc:
0.04-0.05%


Chemical
wave periods
(>1mm):
2-6min




0.08M Na Bromate
0.04M Malonic Acid
0.7M Nitric Acid



▽ - malonic acid, ▣ - sodium bromate
○ - nitric acid (the ★ is the base concentration)



Additive Mfg: Patterned Gelatin




Heterogeneous Gel






Cross Section

3D Pattern


Array of Freestanding Dots in BZ Solution




0.08M Sodium Bromate
0.06M Malonic Acid
0.7M Nitric Acid




Adjacent Patches: Effects of Spacing



Coupled
Osc.



0.08M Sodium Bromate
0.02M Malonic Acid
0.7M Nitric Acid



Summary

1 patch

- Period = 2039 +/- 251


2 close patches

- Inner spacing = 117 +/- 13μm
- Period = 1613 +/- 244
- Ave diff in period: 0-34s


2 far patches

- Inner spacing = 628 +/- 160μm
- Short (clamp) = 1547 +/- 332
- Long (free end) = 1962 +/- 429
- Ave diff in period: 120-751s


Synchrony Comparison to Simulation




Out-of-phase Sync



No Mechanical Coupling



With Mechanical Coupling




Balazs Group Simulation


Putting Blocks Together: Three Patch Actuator






Cut actuator from
patterned sheet



Clamp in PDMS





Gradient in Ru leads to gradient in
strain upon swell-deswell



5x1x0.4mm
cantilever
Period: 30 min.

0.08M Sodium Bromate
0.02M Malonic Acid
0.7M Nitric Acid



1 patch cantilever

- Amp 38.6 +/- 7.4 um
- Period = 1369 +/- 107um

3 patch cantilever


- Amp 162 +/- 36 um
- Period = 1587 +/- 410um

Pattern design and mechanics leads to cooperative swell-deswell with motion amplification of 15x over cube



Half of the cantilever is modeled

Apply temp locally to impart 1.5% strain in patch




1500um

Fixed end

- Max principal strain outside patch: 2.3%
- Max principal strain drops to zero beyond ~300um, <0.5% after 200um
 - Within these distances we expect mechanical effects on coupling

- 1 patch tip displacement = 42um
- 3 patch tip displacement = 191um


Experimental = 38.6um
Experimental = 162um



FEA: Optimal Stain Generator Profile




- Apply 1.5% strain
- Tip displacement = 42.3um




270um

Tip displacement = 28.7um




100um

Tip displacement = 44.1um



Tip displacement = 30.4um




Which shapes give greatest degree deflections?
Which shapes lead to greatest coupling through strain?
How do varying material properties affect behavior?

Next Step: Heterogeneous Autonomic Gels




Patterning: Additive Mfg, 2D Stamping, 3D microtrusses, 3D BZ colloid mixtures




Puopolo, Vaidyanathan OSU

Fibrous Paper





Jacobsen et al. *Adv. Mater.* **19** 2007



Mechanical Design: Bi- / meta- stability for speed; wave interference









Philip Buckohl



Thin Film Solids, 516, 2008, 4070

Model Validation: crosslink network, transduction, material properties

Balazs et al.



Program Status



HT Thermal Shape Memory

PhotoChem-Mechanical

Autonomic Chemo-Mechanical

Building Blocks




w/ L.S. Tan, ATR




Goal: Develop responsive material building blocks & fabrication to establish design tools for functional material systems



w/ T. White & L.S. Tan, ATR





Predictive Models



w/ A. Balazs, UPitt
M. Smith, Hope C.

Fabrication of Devices



w/T. White & M. Smith, Hope C.

